

R200

COATING MACHINE



FIND
MORE



- ▶ Electronic speed control.
- ▶ Electronic ventilation control.
- ▶ Folding vertical structure mounted on wheels.
- ▶ Blower position adjustable on graduated scale.
- ▶ Can be fitted with accessories for partial underneath coating and partial lateral coating.
- ▶ Can be used with Legend, Plus EX, Futura EX and Top EX.

The coating belt is in three sections and installed on a tilting trolley. The loading area can be stopped to increase the accuracy and the positioning times of the product which needs to be coated. The coating area features a mechanical vibration of the coating mesh, which helps to create a uniform coating of the product, and an air blower for controlling the dripping from the chocolate which can be adjusted electronically via the control panel. The latter features an alimentary filter and millimetric adjustment of the working height. The coating speed is electronically adjustable via the operator control panel.

This coating belt was designed for the more demanding workshops and chocolatiers as it allows for precise repetitive processing of any product whilst keeping unchanged the weights and thicknesses.



Technical data

Electrical specification: 220 V monofase - 50-60 Hz
Required power: 0,5 Kw - 16 A - 3 poles.
Dimensions open: h. 1200, w. 1800, d. 600 mm.
Dimensions closed: h. 1800, w. 600, d. 600 mm.